**QSC-2560** Last Revised Scale & Corrosion Inhibitor

2-24-17

405-853-1519

405-853-1519

1 - GENERAL INFORMATION

Manufacturer: Ouick Pump Service LLC

P.O. Box 813

7284 S. Hwy 81

Hennessey, Ok.

Generic Name: Phosphonate **Product Class:** Scale Inhibitor

**DOT Proper Shipping Name** Corrosive Liquid, N.O.S. 8, UN 1760, PG 11,

Phosphate Ester Solution

**NFPA Classification:** 

**Specific Hazard:** N/AP

**DOT/CERCLA RQ:** 

Health: 3

Flammability: 1

Reactivity: 1

2 - SUMMARY OF HAZARDS

**DANGER** 

**Physical Hazards:** Corrosive Liquid

**Acute Health Effects** No Data on Inhalation Hazard

Eve Contact Hazard

**Information Phone:** 

**Emergency Phone:** 

Suspect Skin irritation Hazard Suspect Ingestion Hazard

No Data Found On Skin Absorption No Chronic Health Effects Found

**Chronic Health Effects** 

3 - HAZARDOUS COMPONENTS

Component CAS# %Composition By Volume

No Regulated Hazardous Ingredients

This Product Contains No SARA Section 313 Listed Chemicals.

US TOSCA Inventory: All Components are included in the US TOSCA Inventory

4 - PHYSICAL AND CHEMICAL DATA

**Boiling Point:** pН 1.0 - 2.0N/DA **Freezing Point:** <- 0 F **Dry Point** N/DA **Specific Gravity:** Volatile Charc. Slight

(H2O=1 @ 39.2 F)1.3 **Solubility In Water:** Appreciable Viscosity (Brookfield) N/DA **Stability:** Stable

QSC-2560 Last Revised
Scale & Corrosion Inhibitor 2-24-17

4 - PHYSICAL AND CHEMICAL DATA (continued)

Vapor Specific Gravity: Hazardous Polymerization: Not occur

(Air=1 @ 60-90 F) <1

Appearance And Odor: Conditions And Materials To Avoid:

Yellow Liquid strong bases

Bland Odor strong oxidizing agents

**Hazardous Decomposition Products:** 

Smoke, Carbon Monoxide, Carbon Dioxide, Oxides, Phosphorous Compounds

6 - FIRE AND EXPLOSION

Flash Point: > 200 F Auto ignition Temperature: N/DA

Flammable Limits (% Volume in Air) Lower: ND Upper: ND

Fire And Explosion Hazards:

Containers may explode due build up of internal pressure, if confined to fire. Heat from fire can generate corrosive / combustible vapor.

**Extinguishing Media:** Dry Chemical, CO2, Foam

#### **Special Fire Fighting Procedures:**

Do not enter fire area without proper protection. See Section 4 - Decomposition products possible. Fight fire from a safe distance in a protected location. Heat may build pressure and rupture closed containers, spreading the fire and increasing the risk of burns and injuries. Use water spray/ fog for cooling, but avoid frothing/ steam explosion. Burning liquid may float on water. Notify authorities if liquid enters sewer/public waters.

## 7 - HEALTH HAZARDS

## **Routes Of Exposure:**

#### Inhalation:

No appropriate human or animal health effects data is known to exist on this product.

**QSC-2560** Last Revised 2-24-17

Scale & Corrosion Inhibitor

## 7 - HEALTH HAZARDS

**Eve Contact:** Primary Route

Although no appropriate human or animal effects data are known to exist, this material is expected to cause severe eye irritation.

#### **Skin Absorption:**

Although no appropriate human or animal health effects are known to exist, this material is not expected to be a health hazard by skin absorption.

**Skin Irritation: Primary Route** 

Causes irritation and drying of skin.

**Ingestion:** 

No health effects data is known to exist.

## 8 - PROTECTIVE EQUIPMENT / CONTROL MEASURES

#### **Respiratory Protection:**

If the exposure can exceed the PEL/TLV, use only NIOSH/MSHA approved purifying or supplied air respirator, operated in a positive pressure mode per the NIOSH/MSHA 1981 occupational health guidelines for chemical hazards.

#### **Eve Protection:**

Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles. Contact lenses must not be worn.

## **Skin Protection:**

When skin contact is possible, protective clothing including gloves, apron sleeves, boots head and face protection should be worn. This equipment must be cleaned thoroughly after each use.

### **Engineering Controls:**

Local exhaust may be required to meet exposure standards in addition to general room ventilation.

#### **Other Hygienic Practices:**

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

## **Other Work Practices:**

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/ wash thoroughly before reuse. Shower after work using plenty of soap and water.

QSC-2560 Last Revised Scale & Corrosion Inhibitor 2-24-17

#### 9 - EMERGENCY AND FIRST AID

#### Inhalation:

If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.

#### **Eve Contact:**

In case of eye contact, immediately rinse with clean water for 20 - 30 minutes. Retract eyelids often. Obtain emergency medical attention.

## **Ingestion:**

If swallowed, give water and Do NOT induce vomiting,. Never give anything by mouth to an unconscious person. Seek medical attention.

### **Emergency Medical Treatment Procedures:**

If swallowed do not induce vomiting. For eye contact, continue to rinse eye with clean water for 20 - 30 minutes, retracting eyelids often. Contact ophthalmologist immediately.

#### 10 - SPILL AND DISPOSAL

### **Precautions If Material Is Spilled Or Released:**

Evacuate/limit access. Prevent flow to sewers or public waters. Recover large land spills. Soak up small spills. For spills on water, contain/minimize dispersion and collect. Report per regulatory requirements.

## **Waste Disposal Methods:**

Contaminated product/soil/water may be RCRA/OSHA hazardous waste due to low flash point. Landfill solids at permitted sites. Use registered transporters. Burn concentrated liquids in approved waste incinerators. Assure emissions and effluents comply with application regulations.

#### 11 - ADDITIONAL PRECAUTIONS

### **Handling And Storage Procedures:**

For industrial use only. Keep out of reach of children. Store in tightly closed/properly vented containers away from heat, sparks, open flame or strong oxidizing agents. Store drums with bungs in up position. Carefully vent internal pressure before removing closure.

#### **Decontamination Procedures:**

When cleaning or repairing equipment contaminated with this product, goggles, gloves and boots should be worn. See protective equipment in section 8 for proper respiratory protection.

QSC-2560 Last Revised Scale & Corrosion Inhibitor 2-24-17

#### 12 - SUPPLEMENT

### Note - Qualifiers and codes used in this SDS

EQ	Equal	AP	Approximately
LT	Less Than	GT	Greater Than
TR	Trace	UK	Unknown
N/AP	Not Applicable	N/P	No Appreciable Info.
N/DA	No Data Available	@	At

## 13 - DISCLAIMERS

Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself.

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

This SDS has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1200).