



7284 South HWY 81 - PO Box 813
HENNESSEY, OK 73742

Office: (405) 853-2223

Cell: (405) 853-1519

Fax: (405) 853-2470 quickpump@pdi.net

Product Information Sheet

QC-200

Corrosion Inhibitor

Appearance:	Dark liquid	Density:	7.9 lbs
Odor:	Alcohol	Spec. Gravity:	0.96
Freezing point:	Below -20F	pH:	6.5-7
Flash point:	>110F	Solubility:	Water

Quick Pump Ser. QC-200 is a specific blend of amines and surfactants. It is fresh water soluble and dispersible in oilfield brines. This product is a tenacious filming agent, performing well in water systems and downhole squeeze applications. QC-200 performs well in the presence of H₂S and CO₂. This inhibitor has a wide range of applications and performs well as a cleaner.

QC-200 may be used in disposal systems or in water flood applications. Typical dosage range form 10-40 ppm, depending on the severity of the problem. This product is also very effective for downhole corrosion control. Certain limitations and operating parameters apply; contact your Quick Pump Ser. Professional for particular applications.

Avoid physical contact. Skin irritation may result from prolonged exposure. Rinse exposed areas with soap and water. In the event of eye contact flush with water for 15 minutes and contact physician. For further information regarding this product refer to MSDS sheet.

For pricing and specific information regarding QC-200, please contact your Quick Pump Ser. Sales professional.

QC-200 is available in 55 gallon non-returnable drums.

