



7284 South HWY 81 - PO Box 813  
HENNESSEY, OK 73742

Office: (405) 853-2223

Cell: (405) 853-1519

Fax: (405) 853-2470 quickpump@pldi.net

---

## Product Information Sheet

### **PS-1069**

Paraffin Treating Compound

<b>Appearance:</b>	Light amber liquid	<b>Density:</b>	8.1 lbs
<b>Odor:</b>	Aromatic	<b>Spec. Gravity:</b>	0.98
<b>Freezing point:</b>	Below -20F	<b>pH:</b>	6-7
<b>Flash point:</b>	120F	<b>Solubility:</b>	Oil

Quick Pump Ser. PS-1069 is a specific blend of organic materials designed to both prevent paraffin deposition and dissolve existing paraffin. PS-1069 is highly effective in preventing paraffin deposition in tubing, production lines and treating vessels. PS-1069 Good for hot oil Production tanks with heavy bottoms or hot oil down Tbg. PS-1069 will dissolve solidified paraffin in production systems. It has emulsifying properties to prevent wax emulsions in the interface. PS-1069 is a highly active paraffin compound designed for extreme paraffin problems.

PS-1069 treating rates will vary with the type of crude, temperature and exposure time. Batch treating with 5-55 gallons down the backside and circulating for 8-12 hours, will normally provide excellent cleaning of the system. Continuous injection of 500-1000 PPM for 2-5 days to clean the system, then a reduction to 150-500 PPM; will provide a solution for paraffin control. Tank bottoms can be cleaned by batching 5-15 gallons and circulating back through the surface vessels.

PS-1069 is a flammable liquid! Do not handle or use this product near heat, sparks or open flames. Wear rubber gloves and goggles when handling this product. Avoid contact with body and prolonged breathing of vapor. For further information regarding this product refer to the MSDS sheet.

For pricing and specific information regarding PS-1069, please contact your Quick Pump Serv. sales professional.

PS-1069 is available in 55 gallon non-returnable drums or in bulk.