



7284 South HWY 81 - PO Box 813
HENNESSEY, OK 73742

Office: (405) 853-2223

Cell: (405) 853-1519

Fax: (405) 853-2470 quickpump@pldi.net

Product Information Sheet

QDP-4517

Paraffin & Emulsion Treating Compound

Appearance:	Light amber liquid	Density:	8.1 lbs
Odor:	Aromatic	Spec. Gravity:	0.98
Freezing point:	Below -20F	pH:	6-7
Flash point:	95F	Solubility:	Oil

Quick Pump Ser. QDP-4517 is a specific blend of organic materials designed to prevent paraffin deposition, dissolve existing paraffin, and emulsion control. QDP-4517 is highly effective in preventing paraffin deposition in tubing, production lines and treating vessels, as well as emulsions. QDP-4517 will dissolve solidified paraffin in production systems. It has emulsifying properties to prevent wax, solids, water, and general BS&W emulsions in the interface. QDP-4517 is a highly active compound designed for extreme paraffin and emulsion problems.

QDP-4517 treating rates will vary with the type of crude, temperature and exposure time. Batch treating with 5-55 gallons down the backside and circulating for 8-12 hours, will normally provide excellent cleaning of the system. Continuous injection of 500-1000 PPM for 2-5 days to clean the system, then a reduction to 150-500 PPM; will provide a solution for paraffin and emulsion control. Tank bottoms can be cleaned by batching 5-15 gallons and circulating back through the surface vessels.

QDP-4517 is a flammable liquid! Do not handle or use this product near heat, sparks or open flames. Wear rubber gloves and goggles when handling this product. Avoid contact with body and prolonged breathing of vapor. For further information regarding this product refer to the MSDS sheet.

For pricing and specific information regarding QDP-4517, please contact your Quick Pump Ser. Sales professional.

QDP-4517 is available in 55 gallon non-returnable drums or in bulk.